http://www.irtek-temp.com/

IRtek International

IR150

Measurement Range	: -60ÂºC ~ 1500ÂºC (-76ÂºF ~ 2732ÂºF)
Distance : Spot	: 50 : 1
Resolution	: 0.1Âº
Accuracy	:Â Â±1% for 15ÂºC ~ 35ÂºC Â±2% of reading or 2ÂºC whichever is greater
Emissivity	: adjustable 0.10 ~ 1.00
Response Time	: â‰¤ 1s
Spectral Response	: 8 ~ 14Âµm
Laser Pointer	: Single, Class II, up to 1mW
Sighting System	: Dual beam laser to indicate true diameter of meas. spot
Thermocouple	: K type range: -64 ÂºC ~ 1400 ÂºC (-83.2ÂºF ~ 2552ÂºF) accuracy: Â±1% of reading or Â±1ÂºC (Â±1.8ÂºF) whichever is greater
Power	: 2 x 1.5V (AAA battery)
Size	: 203x47x197mm
Weight	: 386.1g
Standard Accessories	: Hard Case, Instruction Manual, Batteries, Warranty Card, Certificate of Product Conformance, Soft Pouch
Optional Accessories	: Thermocouple Probe (penetration/air/surface), Calibration Certificate

Vendor Information